Applicant : Massimiliano Antonio Poletto et al. Attorney's Docket No.: 12221-014001

Serial No. : 10/701,154

Filed : November 3, 2003

Page : 2 of 16

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A system, comprising:

a plurality of collector devices that are disposed to collect connection information to identify host connection pairs from packets that are sent between nodes on a network; and an aggregator device that receives the connection information from the plurality of collector devices, and which produces a connection table that maps each node on the network to a record that stores information about packet traffic to or from the node.

- 2. (Currently Amended) The system of claim 1 wherein the aggregator determines at least in part from connection patterns derived from the connection table occurrences of network events that indicate potential network intrusions.
- 3. (Currently Amended) The system of claim 2 wherein the aggregator further comprises: a process that collects statistical information on packets that are sent between nodes on a network and which sends the statistical information to the aggregator.
- 4. (Previously Presented) The system of claim I wherein the aggregator device further comprises:
 - a process to detect anomalies in connection patterns; and
 - a process to aggregate detected anomalies into the network events.
- 5. (Original) The system of claim I wherein the collectors have a passive link to devices in the network.

Applicant : Massimiliano Antonio Poletto et al. Attorney's Docket No.: 12221-014001

Serial No. : 10/701.154

Filed :: November 3, 2003

Page : 3 of 16

6. (Previously Presented) The system of claim 4 wherein the anomalies include denial of

service attacks and scanning attacks.

7. (Previously Presented) The system of claim 4 wherein the anomalies include

unauthorized access and worm propagation.

8. (Original) The system of claim 1 wherein the connection table includes a plurality of

records that are indexed by source address.

9. (Original) The system of claim 1 wherein the connection table includes a plurality of

records that are indexed by destination address.

10. (Original) The system of claim I wherein the connection table includes a plurality of

records that are indexed by time.

11. (Original) The system of claim 1 wherein the connection table includes a plurality of

records that are indexed by source address, destination address and time.

12. (Original) The system of claim 1 wherein the connection table includes a plurality of

connection sub-tables to track data at different time scales.

13. (Currently Amended) The system of claim ± 12 wherein the connection sub-tables

include a time-slice connection table that operates on a small unit of time and at least one other

sub-table that operates on a larger unit of time than the time slice sub-table with each sub-table

holding the sum of records received from all collectors during respective units of time.

14. (Currently Amended) A method, comprises:

sending connection information to identify host connection pairs from collected from a

plurality of collector devices to an aggregator; and

Applicant: Massimiliano Antonio Poletto et al. Attorney's Docket No.: 12221-014001

Serial No.: 10/701,154

Filed : November 3, 2003

Page : 4 of 16

producing in the aggregator a connection table that maps each node on the network to a record that stores information about traffic to or from the node.

15. (Previously Presented) The method of claim 14 further comprising: collecting statistical information in the collector devices to send to the aggregator device.

16. (Currently Amended) The method of claim 15 further comprises:

determining occurrences of network anomalies; and

aggregating anomalies into network events that indicate potential network intrusions and communicating occurrences of network events to an operator.

- 17. (Original) The method of claim 14 wherein the connection table includes a plurality of entries that are indexed by source address.
- 18. (Original) The method of claim 14 wherein the connection table includes a plurality of entries that are indexed by destination address.
- 19. (Original) The method of claim 14 wherein the connection table includes a plurality of records that are indexed by time.
- 20. (Original) The method of claim 14 wherein the connection table includes a plurality of records that are indexed by source address, destination address and time.
- 21. (Original) The method of claim 14 wherein the connection table includes a plurality of connection sub-tables to track data at different time scales.
- 22. (Currently Amended) The method of claim <u>21</u> 44 wherein the connection sub-tables include a time-slice connection table that operates on a small unit of time and at least one other

Applicant : Massimiliano Antonio Poletto et al. Attorney's Docket No.: 12221-014001

Serial No.: 10/701,154

Filed : November 3, 2003

Page : 5 of 16

sub-table that operates on a larger unit of time than the time slice sub-table with each sub-table holding the sum of records received from all collectors during respective units of time.

23. (Original) A method of detecting a new host connecting to a network comprises: receiving statistics collected from a host in the network; and

indicating to a console that the host is a new host if, during a period of time T, the host transmits at least N packets and receives at least N packets, and if the host had never transmitted and received more than N packets in any previous period of time with a duration of T.

24. (Previously Presented) A method executed in a computing device for detecting a failed host in a network comprises:

determining in the computing device, if both a mean historical rate of server response packets from a host is greater than M and a ratio of a standard deviation of historical rate of server response packets from the host to a mean profiled rate of server response packets from the host is less than R over a period of time; and

indicating the host as a potential failed host if both conditions are present.